

TURBO 160

ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES UP TO 1600 Kg, 230 Vac



PLUS

With slowdown function both in opening and closing to preserve gate integrity

Electronic and mechanical parts well protected from external agents

Easy maintenance thanks to the horizontal control unit position

With fixing plate included

With 230 Vac control unit CT102 (pag. 142 for technical details)



LCD display



Bronze gears



Sturdy and performing motors

MODELS

CODE	DESCRIPTION	PCS PALLET
SC162	For sliding gates up to 1600 Kg, 230 Vac motor, control unit with slowdown and electric limit switch (1 pc)	36

SC162

MECHANICAL DATA

speed	cm/s	16
torque	Nm	40
working cycle	%	30

ELECTRICAL DATA

control board		CT102
power	Vac	230
consumption	A	2,5
absorbed power	W	600
capacitor	µF	20
thermoprotection	°C	150

GENERIC DATA

protection degree	IP	44
dimensions (L - D - H)	mm	320 - 184 - 260
weight	kg	14,5
working temperature	°C	-20 + 55
gate maximum weight	Kg	1600

ACCESSORIES



CREM-12
M4 iron toothed
rack 30x12 mm
L=1000 mm

PCS 4



TS
Warning board

PC 1