

TURBO 400

ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES UP TO 4000 Kg, 400 Vac



PLUS

Electronic and mechanical parts well protected from external agents

Easy maintenance thanks to the control unit position

Electric brake, to grants safety also on heaviest installations

With 400 Vac control unit CT-400, see page 147 for technical details



Anti-UV rays coating



Sturdy and high-performing motor

MODELS

CODE	DESCRIPTION	PCS PALLET
SC400M	For sliding gates up to 4000 Kg, 400 Vac motor, control unit with slowdown and magnetic limit switch. M6 pinion (1 pc)	4

SC400M

MECHANICAL DATA

speed	cm/s	17
torque	Nm	180
working cycle	%	30*

ELECTRICAL DATA

control board		CT-400
power	Vac	400
consumption	A	2
absorbed power	W	750
thermoprotection	°C	150

GENERIC DATA

protection degree	IP	54
dimensions (L - P - H)	mm	520 - 300 - 585
weight	kg	76
working temperature	°C	-20 + 55
gate maximum weight	Kg	4000

* variable according to the gate weight and dimensions

ACCESSORIES



CREM-30
M6 iron toothed
rack 30x30 mm
L=1000 mm

TS
Warning board

PC 1

PC 1